

# SPECIFICATION

MODEL		SMT-012-030WW	SMT-024-030VW	SMT-036-030VW	
OUTPUT	DC VOLTAGE	12V	24V	36V	
	RATED CURRENT	2.5Amp	1.25Amp	0.83Amp	
	CURRENT RANGE	0~2.5A	0~1.25A	0~0.83A	
	RATED POWER	30W	30W	30W	
	RIPPLE&NOISE(max)	150mV	150mV	150mV	
	CURRENT TOLERANCE	±0.5V	±0.5V	±0.5V	
	SETUP RISE TIME	80ms/110,220VAC	81ms/110,220VAC	82ms/110,220VAC	
	HOLD UP TIME(Typ.)	60ms/110-220VAC	60ms/110-220VAC	60ms/110-220VAC	
INPUT	VOLTAGE RANGE	100~265VAC			
	FREQUENCY RANGE	50~60Hz			
	POWER FACTOR(Typ.)				
	EFFICIENCY(Typ.)	>83%	>83%	>83%	
	AC CURRENT(Typ.)	3.5A/110,220VAC	2.0A/110,220VAC	1.5A/110,220VAC	
	INRUSH CURRENT (Typ.)	COLD START 50A/110~220VAC			
PROTECTION	Short circuit	Protection type:recovers automatically after condition is removed			
	Overload	overload protected@145-160% above peak rating			
	Over temperature	Protection type:Shut down o/p voltage,re-power on to removed			
ENVIRONMENT	WORKING TEMP.	-30~+50°C (Refer to output load derating curve)			
	WORKING HUMIDITY	20~99% RH non-condensing(Waterproof)			
	STORAGE TEMP.,HUMIDITY	-40~+80°C,10~99%RH			
SAFETY&EMC	SAFETY STANDARDS	ETL/ROHS/CE Mark(EMC,LVD),IP67			
	WITHSTAND VOLTAGE	I/P-O/P:1.5KVAC IP-GND:1.5KVAC			
	EMC Test Standards	EN55015:2006;EN61547:1995+2000;EN61000-3-2:2006 EN61000-3-3:1995+A2:2005;EN61346-1:2001;EN61347-2-13:2006			
NOTE	1.All parameters NOT specially mentoned are measured at 110V,220VAC input,rated load and 25°C of ambient temperature.				
	2.Ripple&noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf&10uf parallel				
	3.Tolerance:includes set up tolerance,line regulation and load regulation.				

## Label

● L  
Input

● N  
GND



**Waterproof Constant Voltage Class 2 LED Driver**  
MODEL:SMT-012-030VW

INPUT	AC100~265V	OUTPUT	DC 12V
	47~63Hz		DC 2.5A
			30W

  

Intertek  
5005044

  

Ta: max.50°C

  

Tc: 75°C

  

CAUTION  
RISK OF ELECTRONIC SHOCK.  
SUITABLE FOR WET LOCATIONS

  

ATTENTION  
CONVIENT AUX  
EMPLACEMENTS MOUILLÉS

OUTPUT

Red	+
Black	-